

Algae

Percival® model AL-30L2

Standard SciWhite® lighting



Applications

- Designed for algae that require higher light intensity, short plants that require moderate light intensity and many more applications

Percival's IntellusUltra Controller

The IntellusUltra (C8) control system adapts to nearly any programming style with a large range of options for optimal control over experiments.

- Robust and reliable, industrial-grade integrated hardware design
- Highly flexible programming capabilities for customized configurations and expansion
- Precise, simultaneous control of up to 7 environmental parameters
- Industry-leading experiment protection and system diagnostics

IntellusUltra Touchscreen Interface

This high-resolution touchscreen displays advanced settings and data for fine-tuning experiments, including graphs and charts.

- 10.1" IPS, high resolution display with 10-point multi-touch sensitivity
- Tabular and graphical presentation of chamber programs and parameters
- Highly visible process values and alarm notifications
- Enhanced user feedback menus

Please visit www.percival-scientific.com for more information on our control systems.

SciWhite LED Lighting System

- Two tiers of SciWhite lighting (one on each shelf)
- Programming/real-time control through the IntellusUltra touchscreen
- Intensity up to 440 $\mu\text{moles}/\text{m}^2/\text{s}$ of light irradiance measured @ 6" from LEDs
- Dimmable output from 10-100% in one-percent increments

Airflow/Circulation

- Conditioned air circulates through a rear wall plenum and travels horizontally across each shelf; air then flows vertically upward through the space between the door and shelves back to the unit cooler

AL-30L2 specifications

(subject to change without notice)

Temp Range with all lights on	Interior Space volume		Total Shelving Floor Area	Maximum Growing Height	Exterior Dimensions						Light Intensity 6" from lamps unless otherwise noted	Tiers	
	ft ³	m ³			in	cm	in	cm	in	cm			
°C			ft ²	m ²	in	cm	in	cm	in	cm	μmoles/m ² /s		
7-44±0.5	9.9	0.28	6.1	0.6	10.4	26.4	31	78.7	24.4	61.9	46.2	117.3	Up To 440

Algae Percival model AL-30L2

Cabinet Construction

- Interior constructed of 26-gauge galvanized steel
- Interior floor constructed of 24-gauge polished stainless steel
- Exterior constructed of 24-gauge Galvannealed extra-smooth steel
- NSF-compliant seam design
- Chamber is completely self-contained, suitable for stacking one above the other
- Overall wall thickness is 2" (5.1 cm)
- Highly durable and reflective white coating

Insulation

- Woodless construction using 2" foamed-in-place non-CFC Urethane insulation with 97% closed cell-structure density of 2.2 lbs/ft³

Door

- One door opening 26.7" x 29.8" (67.8 cm x 75.6 cm) provides full access to the chamber interior
- Magnetic gasket provides a tight seal to door frame

Interior Space

- 9.9 ft³ (0.28 m³) with work area of 6.1 ft² (0.6 m²) provided on two tiers

Shelving

- Two tiers of white epoxy coated steel wire shelving (each shelf is 16.5"D x 26.5"W [41.9 cm x 67.3 cm])
- Growing height is 10.4" (26.4 cm) with shelves evenly spaced

Refrigeration

- Self-contained air-cooled condensing unit with hot gas bypass system for continuous compressor operation, extended life and tight temperature control. Continuous running condensing unit ensures precise temperature control by alternately cycling refrigerant and hot gas to coil; also prolongs compressor life and eliminates risk of ice buildup in coil.
- Extended stem solenoid valves for quiet and long life operation
- Rear chamber wall mounted evaporator coil incorporates an air circulation fan
- Heat rejection to ambient (standard chamber) = 2,054 BTU/hr

Temperature Range

- 7°-44°C (±0.5°C) lights on; 2°-44°C (±0.5°C) lights off

Humidity Control (optional)

- Ultrasonic humidifier with advanced RH sensor (H11)
- Ultrasonic humidifier and dehumidifier with advanced RH sensor (H12)
- Ultrasonic humidifier with electronic RH sensor (H14)
- Ultrasonic humidifier and dehumidifier with electronic RH sensor (H15)

See other specification sheets or contact Percival Scientific for additional information.

Options (most popular)

- IntellusUltra Connect (C9)
- Additive CO₂ control
- CO₂ removal system
- Self-contained water-cooled condensing unit
- Dry alarm contacts
- Closed loop dimmable lighting with PAR light sensor (Q22)
- Open loop dimmable lighting per tier (Q23⁺)
- Extended temperature ranges available
- Convenience receptacles

Contact info@percival-scientific.com for additional information.

Electrical Service Requirements

- 115/1/60 with NEMA 5-15P plug provided (with standard chamber)
- RLA=9.9, MCA=12.4

Regulatory Standards

- Electrical Safety: UL-508A, certified and labelled by Percival Scientific under UL file number E340161
- Quality System: ISO 9001:2015, certified under DQS, Inc. under certification number 10017261

Helping You Create Better Science

Percival Scientific controlled environment systems are the culmination of over 60 years of design and manufacturing experience. Our high quality products have been developed through direct partnerships with the scientific community and offer platforms that are highly customizable and provide superior performance. We understand that scientific innovation is bred through creativity, passion, technical expertise and attention to detail, and we are proud to help you create better science.



Percival Scientific, Inc.

505 Research Drive • Perry, IA 50220 USA

800.695.2743 • 515.465.9363 • Fax: 515.465.9464

[www.percival-scientific.com](http://www_percival-scientific.com)